
SnapLock

Quick Change Water Filters

- Potable water applications; commercial, residential, water coolers, caravans, drinking water systems
- Sanitary design for hygienic filter handling
- Bayonet style; easy to use and changeout
- Compact, range of sizes to suit application
- Manual and auto shut off valve head options



SnapLock systems feature quick change sanitary design making the cartridge easy to change and eliminating the handling of

contaminated cartridges. SnapLock heads have a unique patented design featuring a simple quarter turn lock to guarantee correct sealing. Quick connect inlet/outlets are used for easy connection to tubing.

SnapLock heads are available in a range of configurations – please check with Water Filter Services.



Specifications and Operating recommendations

Maximum Termperature – 37°C Maximum Pressure – 900 kPa

Filter must be protected against freezing and direct sunlight.

Operate within pressure and temperature limits.

Carbon cartridges contain a small amount of carbon fines. Flush new cartridges for 2 minutes to remove fines and entrapped air.

Model	Claim	Capacity Itrs	Micron	Length mm
QC2121	sediment	N/A	5	152
QC2211	CTO Cyst	5,675	1	152
QC2231	СТО	5,675	10	152
QC2231P	CTO scale	5,675	10	152
QC2321	CTO GAC	4,750	5	152
QC2123	sediment	N/A	5	254
QC2213	CTO Cyst	9,500	1	254
QC2233	СТО	9,500	10	254
QC2233P	CTO scale	9,500	5	254
QC2124	sediment	N/A	5	305
QC2214	CTO Cyst	11,350	1	305
QC2234	СТО	11,350	10	305
QC2234P	CTO scale	11,350	5	305

CTO = Chlorine taste odour. Check with Water Filter Services for complete range.



1300 720 499

sales@bwtaustralia.com.au www.bwtaustralia.com.au