

Filter Housing – plastic large diameter

Description

Large diameter filter housings offer the versatility to meet large-capacity filtration needs, including high flow and heavy sediment applications. The large housing accepts large diameter cartridges, reducing the number of vessels required for high flow rate applications. Housings are constructed of durable reinforced polypropylene and are available in both 10" and 20" lengths.

Model: FH100



Features & Benefits

- Ideal for a wide range of applications, including residential, commercial and industrial
- Large capacity housing suitable for high flow applications
- Available in 1 and 2 high lengths
- Leak-proof sealing with top-seated o-ring
- Mounting bracket and spanner available
- Pressure relief/bleed on inlet side of cap
- Accepts 4 1/2" diameter cartridges

Application

- Domestic – whole house
- Commercial
- Industrial
- Pools, spas, tanks

Specifications and operating conditions

- Materials of construction: Sump and cap Polypropylene. O Ring Buna N
- Inlet/Outlet ports: 1" bspf
- Length: 1 high 350mm, 2 high 560mm
- Diameter: 180mm at ports
- Temperature range: 4 - 50° C
- Pressure: 620 kPa maximum
- Flow rate: dependent upon cartridge type
- Protect housing from direct sunlight and freezing
- Use pressure limiter to ensure max pressure is not exceeded
- Other models available on request

Part Number Information

• Part Number	FH100B	FH200B	FH100B - K / FH200B - K
• Length mm	300 – 1 high	560 – 2 high	K suffix = KIT
• Colour	Blue/Black	Blue/Black	KIT includes mounting bracket and spanner
• Inlet/Outlet –bspf	1"	1"	